



9000F-X
Pedestrian Trench
Grate Frame Detail #1

Installation in new
concrete

Finish Options:
No Finish or
Galvanized or
Powder Coated.

Specify finish and color
when ordering.

Temporary spreader
bars are tack welded to
frames and must be
removed after frames
are set and concrete
has cured.

Frames are ordered by
the Linear Foot.
Frames are made in
sections such that no
length is greater than
7ft. or shorter than 24".

Please specify if
multiple run lengths
are required to avoid
field modification.

A		B		C		D		Catalog#
Standard	Metric	Standard	Metric	Standard	Metric	Standard	Metric	
4"	102mm	4 5/8"	117mm	4 1/8"	105mm	2 1/8"	54mm	9000F-4
6"	152mm	6 5/8"	168mm	6 1/8"	156mm	4 1/8"	105mm	9000F-6
8"	203mm	8 5/8"	219mm	8 1/8"	206mm	6 1/8"	156mm	9000F-8
12"	305mm	12 5/8"	321mm	12 1/8"	308mm	10 1/8"	257mm	9000F-12
16"	406mm	16 5/8"	422mm	16 1/8"	410mm	14 1/8"	359mm	9000F-16
18"	457mm	18 5/8"	473mm	18 1/8"	460mm	16 1/8"	410mm	9000F-18
20"	508mm	20 5/8"	524mm	20 1/8"	511mm	18 1/8"	460mm	9000F-20
24"	610mm	24 5/8"	625mm	24 1/8"	613mm	22 1/8"	562mm	9000F-24

Frame widths not listed follow the same pattern

This drawing embodies a confidential proprietary design of IRONSMITH, INC. Palm Desert, CA. All design, manufacturing, reproduction, use, sale and other rights regarding the same are expressly reserved. This drawing is submitted under confidential relationship for a specific purpose and the recipient agrees by accepting this drawing not to supply or disclose any information regarding it to any unauthorized person or to incorporate any special feature peculiar to this design in other projects. The information in this drawing may be covered completely or in part by patents pending.

IRONSMITH
41701 Corporate Way #3
Palm Desert, CA 92260
(760)-776-5077
www.ironsmith.biz